



## Legislative components

When the product is dosed at 1 L in 5,000 L of fuel.

Parameter	Method	Range
<b>ACCUTRACE™ PLUS fuel marker</b>	Calculated	12.5 – 18.75 mg/L
<b>Butoxybenzene</b>	HPLC	9.5 – 14.25 mg/L
<b>C.I Solvent red 24</b>	Spectrophotometer	≥ 10.0 mg/L

ACCUTRACE™ is a trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow.

## Physical parameters

Parameter	Method	Range
<b>Density at 15 °C</b>	ASTM D7042 modified	0.94 – 1.02 kg/L
<b>Viscosity at 20 °C</b>	ASTM D7042 modified	< 10 cP
<b>Flash point</b>	IP 34/ ASTM D93	> 61 °C
<b>Water content</b>	Karl Fisher	≤ 0.2 %m/m
<b>Insoluble content</b>	Derived from IP 216 / ASTM D2276	≤ 0.2 %m/m
<b>Temperature of crystallisation</b>	-	< -30 °C

## Typical use and application

This product can be used for the colouration of petroleum products, mineral oils, aliphatic and aromatic hydrocarbon solvents and fuels. The product can be readily pumped, poured or metered directly from the container.

Due to the presence of aromatic solvent in this product, contact with natural rubber must be avoided. For seals and joints the use of PTFE, Viton or similar synthetic products are recommended.

### John Hogg Technical Solutions

Mellors Road, Newbridge, Trafford Park, Manchester M17 1PB

**T:** +44 (0) 161 872 5611 **F:** +44 (0) 161 848 8206 **W:** [www.johnhogg.co.uk](http://www.johnhogg.co.uk) **E:** [info@johnhogg.co.uk](mailto:info@johnhogg.co.uk)




## Typical addition rate

This product is designed to be used at a minimum dosage of 1 litre to 5,000 litres or 200 mL/m<sup>3</sup> to mark fuel oils in accordance with national regulations.


## Appearance

Dyeguard® MC Rouge 0540 is a free-flowing red liquid with a distinct aromatic odour. It is not miscible with water.

## Typical viscosity curve



## Typical density curve



## Shelf life and storage condition

This product is stable for a minimum period of 2 years from the date of manufacture, when stored and handled between 5 °C and 40 °C.

The product should always be stored away from excessive heat sources, direct sunlight and ignition sources. Storage and handling of this product outside the above stated conditions may compromise the product quality.

If product containers are kept sealed, dry, and extreme temperatures are avoided the shelf life of the material is greater than 2 years. The container should be tightly closed when not in use to prevent solvent evaporation.

## Health & safety

Information on how to store and handle this product is included in the SDS which is available from John Hogg.

### Disclaimer

The information contained herein is to the best of our knowledge and belief, accurate. However, since the conditions of handling and of use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by following these suggestions. Nothing contained herein is to be construed as a recommendation for use in violation of any patents or of applicable laws or regulations. © 2019 John Hogg Technical Solutions Ltd, all rights reserved.

### John Hogg Technical Solutions

Mellors Road, Newbridge, Trafford Park, Manchester M17 1PB

T: +44 (0) 161 872 5611 F: +44 (0) 161 848 8206 W: [www.johnhogg.co.uk](http://www.johnhogg.co.uk) E: [info@johnhogg.co.uk](mailto:info@johnhogg.co.uk)